

 **Veriflex® CY PVC (YSLCY) Control Cable**

Eland Product Group: V03

APPLICATION

Veriflex® screened flexible connecting cables for instrumentation and control equipment, for tooling machinery production lines and, in flexible applications for free movement without tensile load. Suitable for use in dry, moist and wet rooms. These cables are not used for outdoor or underground installation.

CHARACTERISTICS**Voltage Rating**
300/500V**Temperature Rating**
Fixed: -40°C to +80°C
Flexed: -5°C to +70°C**Minimum Bending Radius**
Fixed: 4 x overall diameter
Flexed: 12.5 x overall diameter**CONSTRUCTION****Conductor**
Class 5 flexible plain copper**Insulation**
PVC (Polyvinyl Chloride)**Separator**
PET (Polyester Tape)**Screen**
TCWB (Tinned Copper Wire Braid)**Sheath**
PVC (Polyvinyl Chloride)**Core Identification**
● Black with ○ White number
From 3 cores: ● Black with ○ White number + ● Green/Yellow
Colour-coded cores available upon request**Sheath Colour**
● Grey**BSI KITEMARK™ TESTED**

Cables are tested and verified by The Cable Lab® to confirm they meet the quality standards required of the BSI Cable TESTED Verification Kitemark™.

STANDARDS

VDE 0207-363-3, VDE 819-102 (TM54)

Flame Retardant according to IEC/EN 60332-1-2

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved prod

**REGULATORY COMPLIANCE**

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.





DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL THICKNESS OF INSULATION mm	NOMINAL THICKNESS OF OUTER SHEATH mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
V0302001GR000	2	0.5	0.40	0.6	5	35
V0302011GR000	2	0.75	0.40	0.6	5.5	45
V0302021GR000	2	1	0.40	0.7	6.1	56
V0302031GR000	2	1.5	0.40	0.7	6.7	69
V0303001GR000	3	0.5	0.40	0.6	5.4	48
V0303011GR000	3	0.75	0.40	0.7	6	61
V0303021GR000	3	1	0.40	0.7	6.4	71
V0303031GR000	3	1.5	0.40	0.7	7.1	90
V0303041GR000	3	2.5	0.50	0.8	8.6	136
V0304001GR000	4	0.5	0.40	0.7	6	61
V0304011GR000	4	0.75	0.40	0.7	6.5	75
V0304021GR000	4	1	0.40	0.7	7	89
V0304031GR000	4	1.5	0.40	0.7	7.7	114
V0304041GR000	4	2.5	0.50	0.8	9.4	173
V0304051GR000	4	4	0.60	1	11.5	260
V0304061GR000	4	6	0.65	1.1	13.1	358
V0304071GR000	4	10	0.75	1.3	16.7	593
V0304081GR000	4	16	0.75	1.5	19	852
V0304091GR000	4	25	0.90	1.6	23.5	1274
V0304101GR000	4	35	0.95	1.7	26.9	1686
V0305001GR000	5	0.5	0.40	0.7	6.5	73
V0305011GR000	5	0.75	0.40	0.7	7	89
V0305021GR000	5	1	0.40	0.7	7.6	107
V0305031GR000	5	1.5	0.40	0.8	8.6	142
V0305041GR000	5	2.5	0.50	0.9	10.4	216
V0305051GR000	5	4	0.60	1.1	12.7	325
V0305061GR000	5	6	0.65	1.2	14.6	449
V0305071GR000	5	10	0.75	1.4	18.5	738
V0305081GR000	5	16	0.75	1.5	20.9	1050
V0305091GR000	5	25	0.90	1.7	26.1	1588
V0307001GR000	7	0.5	0.40	0.7	7	89
V0307011GR000	7	0.75	0.40	0.7	7.6	112
V0307021GR000	7	1	0.40	0.8	8.4	139
V0307031GR000	7	1.5	0.40	0.8	9.3	180
V0307041GR000	7	2.5	0.50	1	11.5	283
V0312001GR00000	12	0.5	0.40	0.8	9.2	143
V0312011GR00000	12	0.75	0.40	0.8	10	181
V0312021GR00000	12	1	0.40	1	11.2	230
V0312031GR00000	12	1.5	0.40	1.1	12.7	307
V0318011GR00000	18	0.75	0.40	1.1	12.2	274
V0318021GR00000	18	1	0.40	1.1	13.2	331
V0318031GR00000	18	1.5	0.40	1.2	14.9	443
V0325011GR00000	25	0.75	0.40	1.1	13.2	282
V0325021GR00000	25	1	0.40	1.2	15.8	444
V0325031GR00000	25	1.5	0.40	1.3	17.9	596



Click here for more information:

elandcables.com | [Veriflex CY PVC YSLCY Control Cable](#)

ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITIES 30°C CONTINUOUS LOADING A	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
0.5	9	39
0.75	12	26
1	15	19.5
1.5	18	13.3
2.5	26	7.98
4	34	4.95
6	44	3.3
10	61	1.91
16	82	1.21
25	108	0.780
35	135	0.554

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.