

GM-FS Locknut





Eland Product Group: HUM

APPLICATION

A polyamide locknut suitable for use with our HSK-K Gland. Reinforced with glass fibre, this hexagonal counter locknut secures fixings on metric thread cable glands.

CONSTRUCTION

Gland Material

Polyamide V0 according to UL 94

STANDARDS

UL94





The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

CHARACTERISTICS

Operating Temperature

-40°C to +100°C


Colours

■ Grey ■ Black

Note

Other colours on request





DESCRIPTION

IG	H mm	₩ mm
M 12 x 1.5	5	17
M 16 x 1.5	5	22
M 20 x 1.5	6	27
M 25 x 1.5	6.5	32
M 32 x 1.5	7	41
M 40 x 1.5	7	50
M 50 x 1.5	8	60
M 63 x 1.5	8	75
	M 12 x 1.5 M 16 x 1.5 M 20 x 1.5 M 25 x 1.5 M 32 x 1.5 M 40 x 1.5 M 50 x 1.5	M 12 x 1.5 5 5 5 M 16 x 1.5 5 6 M 20 x 1.5 6 M 25 x 1.5 7 M 40 x 1.5 7 M 50 x 1.5 8

^{*}Eland Part No. shown above designate the colour (*). For each colour substitute * for a colour code as listed below. e.g. HUMLECM12MNLGR0= Grey

Colour Codes

COLOUR	Black	Grey
CODE	ВК	GR

ISSUE NO 01-03 -2014

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.