

Neoprene Sleeving



Eland Product Group: **FCA**

APPLICATION

Neoprene sleeving is primarily used for the identification and bundling of cables. It is particularly useful for binding the ends of braided mains leads into plugs and portable equipment.



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

CONSTRUCTION

Material

Highly elastic extruded neoprene

CHARACTERISTICS

Colours

● Black ● Blue ● Brown ● Green ● Grey ● Orange ● Pink
● Red ● Yellow

DIMENSIONS

| ELAND PART NO. | MINIMUM CABLE DIAMETER | MAXIMUM CABLE DIAMETER | PACK QUANTITY |
|----------------|------------------------|------------------------|---------------|
| | mm | mm | |
| H12 x 20 | 1.7 | 3.6 | 100 |
| H20 x 30 | 3 | 6 | 100 |
| H30 x 25 | 4.5 | 9 | 100 |
| H50 x 25 | 7.5 | 15 | 100 |
| H75 x 25 | 10 | 22.5 | 50 |
| H100 x 25 | 15 | 30 | 50 |

*Also available as continues length's